

Renovation

ACCESS DOOR

The Nystrom Renovation Access Door is a lighter gauge alternative to the Architectural Door (*page 5*). The panel features an industry-leading design to provide superior durability and functionality.

DETAILS

DOOR 20 gauge Steel

FRAME 20 gauge Steel

SIZE

- Min: 6 inches by 6 inches
- Max: 24 inches by 72 inches or 48 inches by 48 inches

INSTALLATION Ceiling or Wall

FLANGE 1 inch Exposed

HINGE Concealed Spring Button

PAN DEPTH 1/2 inch

FINISH White Powder Coat



ORDER GUIDE

BASE	FLANGE	LATCH	WIDTH	X	LENGTH	OPTIONS
E				X		
	T 1 inch Flange	C Screwdriver Cam Latch L Key Operated Cam Lock	Standard Sizes (W x L) 6" x 6" 8" x 8" 10" x 10" 12" x 12" 12" x 18" 12" x 24" 14" x 14" 16" x 16"	16" x 20" 18" x 18" 18" x 24" 20" x 30" 22" x 22" 22" x 30" 24" x 24" 24" x 30"	24" x 36" 24" x 48" 30" x 30" 30" x 36" 32" x 32" 36" x 36"	B Galvannealed G Gasketing

Rough opening is door size + 1/4 inch minimum. Additional sizes available, call for more information.

Recessed

ACCESS DOOR

The non-rated Recessed Access Door provides access through openings in wall or ceiling surfaces. This door is designed to receive 5/8 inch drywall to match the surrounding surfaces.

DETAILS

DOOR 16 gauge Steel

FRAME 16 gauge Steel

SIZE

- Min: 6 inches by 6 inches
- Max: 24 inches by 36 inches

INSTALLATION Ceiling

FLANGE None, Drywall Bead or Plaster Bead

HINGE Concealed Pivoting Rod

PAN DEPTH 5/8 inch

FINISH White Powder Coat or None



ORDER GUIDE

BASE	FLANGE	LATCH	WIDTH	X	LENGTH	OPTIONS
R				X		
	A No Flange P Plaster Bead W Drywall Bead	C Screwdriver Cam Latch L Key Operated Cam Lock M Mortise Lock (1-1/8") Prep	Standard Sizes (W x L) 8" x 8" 12" x 12" 16" x 16" 18" x 18"	20" x 30" 24" x 24" 24" x 30" 24" x 36"		B Galvannealed S Stainless Steel, Type 304

*Rough opening is door size + 1/4 inch minimum. Additional sizes available, call for more information.
Ceiling application only.