



### DETAILS

**DOOR** Welded Aluminum, Drywall Infill

**FRAME** Welded Aluminum

#### SIZE

- Min: 8 inches by 8 inches
- Max: 40 inches by 40 inches

**INSTALLATION** Ceiling or Wall

**LATCH** Push Latch

**HINGE** Welded Pin

**FINISH** Mill

### ORDER GUIDE

BASE	APPLICATION	WIDTH	X	LENGTH	OPTIONS	INFILL
<b>RG</b>			<b>X</b>			
	<b>B</b> STB Pin Hinged	Standard Sizes (W x L)			<b>C</b> Screwdriver Cam Latch	<b>500</b> ½ inch drywall
	<b>BR</b> Removable Door	8" x 8"	16" x 16"	24" x 24"	<b>D</b> Double Door	
	<b>T</b> Tile	12" x 12"	20" x 20"		<b>L</b> Key Operated Cam Lock	<b>625</b> ⅝ inch drywall

# Drywall

## ACCESS DOOR

The Drywall Access Door comes with standard ½ inch or ⅝ inch drywall installed in the door pan. Available in five standard sizes and three door styles for various application requirements.

### FEATURES

**PUSH LATCHING DOOR** Once installed, this door gives the desired appearance architects look for. The door quickly and easily opens and closes with the magnetic push-catch latch.

**SAFETY CORD** For overhead applications, this safety cord supports the door while opening the unit.

### APPLICATION



STB Pin Hinge



Removable Door



Tile

### OPTIONS



Screwdriver Cam Latch



Key Operated Cam Lock



Double Door

# Recessed

## ACCESS DOOR

The non-rated Recessed Access Door provides access through openings in wall or ceiling surfaces. This door is designed to receive ⅝ inch drywall to match the surrounding surfaces.

### DETAILS

**DOOR** 16 gauge Steel

**FRAME** 16 gauge Steel

#### SIZE

- Min: 6 inches by 6 inches
- Max: 24 inches by 36 inches

**INSTALLATION** Wall and Ceiling

**FLANGE** None, Drywall Bead or Plaster Bead

**HINGE** Concealed Pin

**PAN DEPTH** ⅝ inch

**FINISH** White Powder Coat or None



### ORDER GUIDE

BASE	FLANGE	LATCH	WIDTH	X	LENGTH	OPTIONS
<b>R</b>				<b>X</b>		
	<b>A</b> No Flange	<b>C</b> Screwdriver Cam Latch	Standard Sizes (W x L)			<b>B</b> Galvannealed
	<b>W</b> Drywall Bead	<b>L</b> Key Operated Cam Lock	8" x 8"	20" x 30"	24" x 24"	
	<b>P</b> Plaster Bead	<b>M</b> Mortise Lock (1 ½ inch) Prep	12" x 12"	24" x 24"	24" x 30"	
			16" x 16"	24" x 30"	18" x 18"	24" x 36"

Rough opening is door size + ¼ inch minimum. Additional sizes available, call for more information.