

Retrofit

ROOF HATCH

The retrofit roof hatch allows you to replace your damaged or worn-out hatch without compromising your roofing system, saving you time and labor.

BENEFITS

PRESERVE THE INTEGRITY OF YOUR ROOFING SYSTEM

Retrofit roof hatch attaches to existing curbs without compromising the roofing system, or warranty.

LONG LASTING SOLUTION Our standard red oxide powder-coat finish provides outstanding corrosion resistance and color retention.


MAINTAINS SAFE OPERATION & EGRESS Low-profile 4" curb & safety railing ready.



FINISHES



Mill
Aluminum



2B Matte
Stainless Steel*



ANSI 70 Gray
Powder Coat



High Reflectance White
Powder Coat

SINGLE POINT LATCH

LATCH Zinc-plated steel latch with exterior and interior turn handles and padlock hasps.

SPRING Gas-spring with damper & coil type spring in telescopic tubes for smooth controlled lift assistance.

HINGE Heavy-duty pintle hinge with stainless steel hinge pin

PULL HANDLE Interior safety pull down handle, yellow powder coat

STANDARD MODELS

RED STEEL	ALUMINUM	THERMALLY BROKEN	SIZE
RHRG36X30S1T	RHRA36X30S1T	RHRT36X30S1T	36X30
RHRG36X36S1T	RHRA36X36S1T	RHRT36X36S1T	36X36
RHRG48X48S1T	RHRA48X48S1T	RHRT48X48S1T	48X48
RHRG30X54S1T	RHRA30X54S1T	RHRT30X54S1T	30X54
RHRG30X96S1T	RHRA30X96S1T	RHRT30X96S1T	30X96

Additional sizes and options available, call for more information.

DETAILS

MATERIAL

- 11 gauge Aluminum, mill finish
- Steel 14 gauge galvalume, gray powder coat
- Stainless steel

COVER Formed metal cover with liner, stiffened to withstand a live load of 40psf with a max deflection of $\frac{1}{150}$ the span

CURB 4" tall Double wall curb with Stainless steel mounting clips

INSULATION 1 inch polyiso R-6 in curb, 1 inch polystyrene in cover. Optional 3 inch single layer foil faced polyiso in curb and cover; R-20.3.

GASKET Extruded EPDM adhesive-backed gasket seal continuous around cover

HOLD-OPEN ARM Zinc-plated steel automatic hold open arm locks cover in open position