



SPECIFICATIONS:

- (1) **COVER:** 11 GA ALUM COVER STIFFENED TO WITHSTAND A LIVE LOAD OF 40PSF WITH A MAX DEFLECTION OF 1/150 OF THE SPAN
- $\langle 2 \rangle$ **LINER:** 18 GA ALUM
- (3) CURB AND COUNTERFLASH W/ EZ TAB:
 - 11 GA ALUM
- 4 FINISH: MILL FINISH
- $\langle 5 \rangle$ **SPRING/HINGE ASSEMBLY:** ZINC PLATED STEEL TAMPER-PROOF HINGE CONTAINED WITHIN SPRING/HINGE ASSEMBLY. TELESCOPIC TUBES CONTAIN COIL STEEL COMPRESSION SPRINGS FOR LIFT ASSISTANCE
- 6 HOLD OPEN ARM: LOCKS COVER IN FULLY OPEN POSITION -ZINC PLATED STEEL WITH RED POLYPROPYLENE GRIP HANDLE PULL RELEASE
- (7) LATCH: 2 POINT ROTARY LATCH HOLDS COVER CLOSED AGAINST WIND UPLIFT. INTERNAL AND EXTERNAL TURN HANDLES WITH PADLOCK HASPS

- INSULATION:
 - 1" POLYISO (R6) CURB, 1" POLYSTYRENE (R4) COVER
- GASKET: ADHESIVE BACKED EPDM RUBBER EXTRUSION
- **SIZING:** WIDTH X LENGTH DIMENSIONS ARE MEASURED INSIDE CURB TO INSIDE CURB WHERE THE WIDTH IS HINGE TO LATCH AND LENGTH IS HINGED SIDE WITH SPRINGS

ROOF HATCH SIZE 30" (WIDTH) x 96" (LENGTH) CLEAR OPENING 21.94" (WIDTH) x 94.31" (LENGTH) ROUGH OPENING 30" (WIDTH) x 96" (LENGTH)

ARCHITECT CONTRACTOR: QTY: PART#: RHHA30X96S1T TITLE: nystrom Roof Hatch, Hurricane, 30x96, Sngl Dr, Zinc Hdw, 9300 73rd Avenue North. Alum, Mill, Sngl Wall Curb Minneapolis, MN 55428 NAME DATE SIZE DWG. NO. REV RHHA30X96S1T Α DRAWN SJB 11/5/15 RELEASED WEIGHT: 190.7 SHEET 1 OF 2

MIAMI-DADE COUNTY APPROVED

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NYSTROM. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NYSTROM IS PROHIBITED.

PROJECT:

