

SPECIFICATIONS:

- (1) COVER: 11 GA ALUM COVER STIFFENED TO WITHSTAND A LIVE LOAD OF 40PSF WITH A MAX DEFLECTION OF 1/150 OF THE SPAN
- (2) LINER: 18 GA ALUM
- $\overline{\langle 3 \rangle}$ CURB AND COUNTERFLASH W/ EZ TAB:
- 11 GA ALUM
- 4 FINISH: MILL FINISH
- (5) SPRING/HINGE ASSEMBLY: ZINC PLATED STEEL TAMPER-PROOF HINGE CONTAINED WITHIN SPRING/HINGE ASSEMBLY. TELESCOPIC TUBES CONTAIN COIL STEEL COMPRESSION SPRINGS FOR LIFT ASSISTANCE
- 6 HOLD OPEN ARM: LOCKS COVER IN FULLY OPEN POSITION -
- ZINC PLATED STEEL WITH RED POLYPROPYLENE GRIP HANDLE PULL RELEASE
- (7) LATCH: 2 POINT ROTARY LATCH SLAM LATCH HOLDS COVER CLOSED AGAINST 90 PSF WIND UPLIFT. INTERNAL AND EXTERNAL TURN HANDLES WITH PADLOCK HASPS

- (8) INSULATION:
- 1" POLYSTYRENE (R4) IN COVER, AND 1" POLYISO (R6) IN CURB

3['] 1/2" -MOUNTING

FLANGE

- (9) GASKET: ADHESIVE BACKED EPDM RUBBER EXTRUSION
- 10 SIZING: WIDTH X LENGTH DIMENSIONS ARE MEASURED INSIDE CURB TO INSIDE CURB WHERE THE WIDTH IS HINGE TO LATCH AND LENGTH IS HINGED SIDE WITH SPRINGS

ROOF HATCH SIZE " (WIDTH) X " (LENGTH)

CLEAR OPENING " (WIDTH) X " (LENGTH)

ROUGH OPENING " (WIDTH) X " (LENGTH)

PROJECT: ARCHITECT: CONTRACTOR: QTY: PART#: Roof Hatch, Personnel Series, Sngl Dr, Zinc Hdw, Alum Curb and Cover, Mill Finish, Sngl Wall Curb 9300 73rd Avenue North Minneapolis, MN 55428 NAME DATE SIZE DWG. NO. REV Α DRAWN ELW 9/10/12 RELEASED WEIGHT: VARIES SHEET 1 OF 2

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NYSTROM. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NYSTROM IS PROHIBITED.

2

LENGTH

SECTION B-B

1

