

March 2026

RE: Sustainability Statement

Nystrom certifies and provides the following information for use in achieving LEED v5 credit for specification of the following:

Product: Security Roof Hatches

Models: RHSA, RHSG, RHSB

Final Assembly Location: Minneapolis, MN

LEED v5 Credit Contributions

Category: Materials and Resources

Credit: MRc3 – Low-Emitting Materials (2 Points Possible)

Nystrom Security Roof Hatches consist of at least 94% powder coated, plated or anodized metals, which LEED considers inherently non-emitting sources of VOCs.

Category: Materials and Resources

Credit: MRc4 – Building Product Selection and Procurement (5 Points Possible)

Nystrom has demonstrated achievement in two criteria areas for Security Roof Hatches:

- *Human Health:* A published, complete Health Product Declaration (HPD) is available for [Security Roof Hatches](#), with full disclosure of known hazards of all substances present at or above 1,000 ppm (0.1%) and Pre-Checked for LEED [Score: 1]
- *Circular Economy:* Nystrom Security Roof Hatches are constructed primarily of Aluminum and/or Steel, with the following recycled content: [Score: Up to 1]
 - RHSA (Aluminum Curb and Cover)
 - Minimum 78% Aluminum Alloy (40-80% pre-consumer; 10-30% post-consumer)
 - Minimum 17% Steel Alloy (default 25% post-consumer)
 - RHSG (Steel Curb and Cover)
 - Minimum 96% Steel Alloy (default 25% post-consumer)
 - RHSB (Steel Curb and Aluminum Cover)
 - Minimum 60% Steel Alloy (default 25% post-consumer)
 - Minimum 34% Aluminum Alloy (40-80% pre-consumer; 10-30% post-consumer)

9300 73rd Avenue North, Minneapolis, MN 55428

Phone (800) 547-2635

Fax (866) 900-1959

Email: info@nystrom.com