SmokEscape<sup>™</sup> (Single Door)

**SMOKE VENT** 

Nystrom's Single Door SmokEscape Smoke Vent, engineered with a metal cover, is ideal for factory, storage and warehouse occupancies, and hoistways. The single door smoke vent offers the largest effective vent area.

# **FEATURES**

**GREATER EFFECTIVE VENT AREA** Reduce the number of smoke vents required on the roof with the industry's largest 48 x 96 single door smoke vent.

OPTIONAL LOUVERED CURB Add additional ventilation with louvered curbs. Ideal for use in elevator shafts and hoistways.



## **DETAILS**

- Aluminum: 11 gauge, mill finish
- Steel: 14 gauge, ANSI 70 Gray powder coat

**COVER** Formed metal cover with liner, internally stiffened to withstand a live load of 40psf

**CURB** Single wall curb with EZ tab counterflash and mounting flange

**INSULATION** 1 inch Polyiso R-6 in cover and around curb.

**GASKET** Extruded EPDM adhesive backed gasket seal, continuous around

**HINGE** Heavy-duty pintle hinge with stainless steel hinge pins

**SPRING** Gas spring with damper opens cover against 10psf snow load

HOLD OPEN ARM Zinc plated steel automatic hold open arm locks cover in open position

**LATCH** Zinc plated steel rotary latch designed to hold covers closed against 30psf wind uplift. Opens manually by external and internal pull cables. Opens automatically with a fusible link at standard temperature 165°F.

CERTIFICATIONS UL 793 Listed, FM 4430 Approved

# 3-1/2' Width

# **ORDER GUIDE**

BASE	MATERIAL	WIDTH	Х	LENGTH	DOOR	CURB	ELECTRIC	LINK TEMP (°F)	CLOSING	-	OPTIONS
svs			Х							-	
	A Aluminum Curb & Cover B Galvanneal Curb / Aluminum Cover	Standard Sizes (W x L) 30" x 30" 36" x 30" 36" x 36" 48" x 48" 48" x 72" 48" x 96"			<b>S</b> Single Door	1 Single Wall 2 Double Wall 3 Curb Mount	N No Electrical L 24VDC/24VAC H 110VAC / 240VAC	165 350 212 360 280 450	R Rooftop Close		OP1 Door Position Sensor  B Burglar Bars/Fall Protection Screen  SFM FM Labeled
	<b>G</b> Galvanneal Curb & Cover	Additiona also avail									