


MODEL N3.25E

(TWO STAGE RIBBED ABRASIVE BARS)

SPECIFICATIONS:

- 1. **BASE:** EXTRUDED ALUMINUM ALLOY 6063 T-52
- 2. **ECOTREAD:** RECYCLED RUBBER SHEET
8MM RECYCLED RUBBER GRANULES
ENCAPSULATED IN A WEAR AND WATER
RESISTANT ELASTOMERIC NETWORK. 2 PARTS
- 3. **BASE FINISH:** MILL
- 4. **POURED CONCRETE STAIRS:** NOSING SHALL
TERMINATE NO MORE THEN 3" FROM END OF
STEPS
- 5. **CONCRETE FILLED STEEL PAN STAIRS:** NOSING
SHALL BE FULL LENGTH OF STEPS, LESS 1/8"
CLEARANCE
- 6. **COLOR:** BLACK (STANDARD), SAFETY YELLOW,
BLACK-BLUE, BLACK-GRAY
- 7. **LENGTH:** 12'0" MAXIMUM

LENGTH	QTY	COLOR

PROJECT:					
ARCHITECT:					
CONTRACTOR:					
QTY:					
PART#:		STTB-N3.25E-ECO			
 9300 73rd Avenue North Minneapolis, MN 55428		TITLE: Two Stage Rib, Stair Tread, Ecotread Insert No Nose, Aluminum, Extruded Anchor			
	NAME	DATE	SIZE	DWG. NO.	REV
DRAWN	DKL	8/21/24	A	Nystrom STN STTB-N3.25E-ECO ShpDr	A
RELEASED	TR	8/21/24	WEIGHT: 2 LB		SHEET 1 OF 1