

1" PHOTOLUMINESCENT INSERT


MODEL STSM-P3E-ECO

SPECIFICATIONS:

- ① **BASE:** EXTRUDED ALUMINUM ALLOY 6063 T-6
- ② **ECOTREAD:** RECYCLED RUBBER SHEET
8MM RECYCLED RUBBER GRANULES
ENCAPSULATED IN A WEAR AND WATER
RESISTANT ELASTOMERIC NETWORK. 2 PART
EPOXY, LOCKED INTO EXTRUDED CHANNELS



PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NYSTROM. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NYSTROM IS PROHIBITED.

| | | | | |
|--|------|--|----------|--------------|
| PROJECT: | | | | |
| ARCHITECT: | | | | |
| CONTRACTOR: | | | | |
| QTY: | | | | |
| PART#: | | | | |
|  9300 73rd Avenue North Brooklyn Park, MN 55428 | | TITLE: Stair Tread, Single Stage, 3 1/2" x 1 1/8" Ribbed, Photoluminescent Insert, Short Tip Nose, Alum Extruded Anchor, 1" Photoluminescent Insert | | |
| NAME | DATE | SIZE | DWG. NO. | REV |
| DRAWN | DKL | 3/6/19 | A | 1 |
| RELEASED | TR | 3/6/19 | WEIGHT: | SHEET 1 OF 1 |