



### MODEL P3.375E-ECO

(TWO STAGE RIBBED ABRASIVE BARS)

**SPECIFICATIONS:**

- ① **BASE:** EXTRUDED ALUMINUM ALLOY 6063 T-5
- ② **ECOTREAD:** RECYCLED RUBBER SHEET  
8MM RECYCLED RUBBER GRANULES  
ENCAPSULATED IN A WEAR AND WATER  
RESISTANT ELASTOMERIC NETWORK. 2 PARTS
- 3. **BASE FINISH:** MILL
- 4. **POURED CONCRETE STAIRS:** NOSING SHALL  
TERMINATE NO MORE THEN 3" FROM END OF  
STEPS
- 5. **CONCRETE FILLED STEEL PAN STAIRS:** NOSING  
SHALL BE FULL LENGTH OF STEPS, LESS 1/8"  
CLEARANCE
- 6. **COLOR:** BLACK (STANDARD), SAFETY YELLOW
- 7. **LENGTH:** 120" MAXIMUM
- 8. **UL 1994 LISTED:** COMBINED WIDTH OF PHOTO-  
LUMINESCENT MATERIAL SHALL NOT BE LESS  
THAN 1"

LENGTH	QTY	COLOR

PROJECT:		
ARCHITECT:		
CONTRACTOR:		
QTY:		
PART#:	STTB-P3.375E-ECO	
<b>nystrom</b> 9300 73rd Avenue North Minneapolis, MN 55428	TITLE: Two Stage Rib, Stair Tread, Bar Ribbed Ecotread, Short Nose, Alum Extruded Anchor,	
NAME DATE	SIZE DWG. NO.	REV
DRAWN DKL 9/14/21	A Nystrom STTB-P3.375E-ECO ShpDr	A
RELEASED GLN 9/14/21	WEIGHT: 2 LB	SHEET 1 OF 1

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NYSTROM. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NYSTROM IS PROHIBITED.