



PHOTOLUMINESCENT GRIT TAPE

### MODEL P3.375E-T-ECO

(TWO STAGE RIBBED ECO-TREAD BARS)

**SPECIFICATIONS:**

- ① **BASE:** EXTRUDED ALUMINUM ALLOY 6063 T-6
- ② **ECOTREAD:** RECYCLED RUBBER SHEET 8MM, RECYCLED RUBBER GRANULES ENCAPSULATED IN A WEAR AND WATER RESISTANT ELASTOMETRIC NETWORK
- 3. **BASE FINISH:** MILL
- 4. **POURED CONCRETE STAIRS:** NOSING SHALL TERMINATE NO MORE THEN 3" FROM END OF STEPS
- 5. **CONCRETE FILLED STEEL PAN STAIRS:** NOSING SHALL BE FULL LENGTH OF STEPS, LESS 1/8" CLEARANCE
- 6. **COLOR:** BLACK (STANDARD), SAFETY YELLOW,

- 7. **LENGTH:** 12'0" MAXIMUM
- 8. **UL 1994 LISTED:** COMBINED WIDTH OF PHOTO-LUMINESCENT MATERIAL SHALL NOT BE LESS THAN 1"

LENGTH	QTY	COLOR

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NYSTROM. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NYSTROM IS PROHIBITED.

PROJECT:			
ARCHITECT:			
CONTRACTOR:			
QTY:			
PART#:		STTM-P3.375E-T-ECO	
TITLE:		Two Stage Rib, Stair Tread, Bar Ribbed Eco-Tread Short Nose, Alum Extruded Anchor, Black, Photoluminescent Grit Tape	
DRAWN		DKL	9/24/21
RELEASED		TR	9/24/21
NAME	DATE	SIZE	DWG. NO.
		A	Nystrom STN STTM-P3.375E-T-ECO ShpDr
WEIGHT:			REV A