





B

B




A

A

SPECIFICATIONS:

- ① **BASE: 319 CAST ALUMINUM**
- ② **ABRASIVE: SILICON CARBIDE ABRASIVE , CROSSHATCH PATTERN 1/8" DEEP**
- 3. **FINISH: SAND CAST**
- 4. **POURED CONCRETE STAIRS: NOSING SHALL TERMINATE NO MORE THAN 3" FROM SIDE OF STEPS**
- 5. **LENGTH: 6" MINIMUM 6'-0" MAXIMUM**
- 6. **WING ANCHORS: INSTALLED, STEEL ANCHORS, AND STAINLESS STEEL HARDWARE**

LENGTH ±1/8	QTY

PROJECT:					
ARCHITECT:					
CONTRACTOR:					
QTY:					
PART#:		STCA-C3C			
 9300 73rd Avenue North Minneapolis, MN 55428		TITLE:			
		Stair Tread, Cast Series 3", Cast Aluminum Crosshatch Short Nosing for Concrete, Wing Anchor Installed			
	NAME	DATE	SIZE	DWG. NO.	REV
DRAWN	DKL	10/13/23	A	STCA-C3C	C
RELEASED	GLN	10/13/23	WEIGHT: 1.20 LB/FT	SHEET 1 OF 1	

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NYSTROM. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NYSTROM IS PROHIBITED.