



SPECIFICATIONS:

- ① BASE: 319 CAST ALUMINUM
- ② ABRASIVE: SILICON CARBIDE ABRASIVE , CROSSHATCH PATTERN 1/8" DEEP
- 3. FINISH: SAND CAST
- 4. POURED CONCRETE STAIRS: NOSING SHALL TERMINATE NO MORE THEN 3" FROM END OF STEPS
- 5. LENGTH: 6" MINIMUM 6'-0" MAXIMUM

LENGTH ± 1/8	QTY

PROJECT:					
ARCHITECT:					
CONTRACTOR:					
QTY:					
PART#:		STCA-P2C			
 9300 73rd Avenue North Minneapolis, MN 55428		TITLE: Stair Tread, Cast Series 2", Cast Aluminum Crosshatch Short Nosing for Pan, Bolt Anchor			
		NAME	DATE	SIZE	DWG. NO.
DRAWN	SJB	3/31/11	A	STCA-P2C	A
RELEASED	DWO	3/31/11	WEIGHT: 1.20 LB/FT	SHEET 1 OF 1	

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NYSTROM. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NYSTROM IS PROHIBITED.