


**MODEL A11D-ECO**  
(RENOVATION ECO-TREAD RIBS)

**SPECIFICATIONS:**

- ① **BASE:** EXTRUDED ALUMINUM ALLOY 6063 T-6
- ② **ECOTREAD:** RECYCLED RUBBER SHEET  
8MM RECYCLED RUBBER GRANULES  
ENCAPSULATED IN A WEAR AND WATER  
RESISTANT ELASTOMERIC NETWORK. 2 PART  
EPOXY, LOCKED INTO EXTRUDED CHANNELS
- 3. **BASE FINISH:** MILL
- 4. **POURED CONCRETE STAIRS:** NOSING SHALL  
TERMINATE NO MORE THEN 3" FROM END OF STEPS
- 5. **CONCRETE FILLED STEEL PAN STAIRS:** NOSING  
SHALL BE FULL LENGTH OF STEPS, LESS 1/8"  
CLEARANCE
- 6. **COLOR:** BLACK (STANDARD), SAFETY YELLOW

- 7. **LENGTH:** 12'0" MAXIMUM
- 8. COUNTER SUNK HOLES PRE-DRILLED FOR A #10  
FASTENER SPACED 3" FROM ENDS AND  
APPROXIMATELY 12" TO 15" O.C.
- 9. UL 1994 LISTED: COMBINED WIDTH OF PHOTO-  
LUMINESCENT MATERIAL SHALL NOT BE LESS  
THAN 1"

LENGTH	QTY	COLOR

PROJECT:					
ARCHITECT:					
CONTRACTOR:					
QTY:					
PART#:		STRB-A11D-ECO			
 9300 73rd Avenue North Minneapolis, MN 55428		TITLE:			
		V505S, Stair Tread, Recycled Rubber, 18 Eco-Tread Ribs Long Nose Angled, Drilled For Bolt In,			
NAME	DATE	SIZE	DWG. NO.	REV	
DRAWN	DKL	3/10/20	A	Nystrom STN STRB-A11D-ECO ShpDr	A
RELEASED	TR	3/10/20	WEIGHT: 4.7 LB	SHEET 1 OF 1	

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NYSTROM. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NYSTROM IS PROHIBITED.