


**MODEL L1.875E-ECO**

(SINGLE STAGE ECO-TREAD RIBS)

**SPECIFICATIONS:**

- ① **BASE:** EXTRUDED ALUMINUM ALLOY 6063 T-5
- ② **ECOTREAD:** RECYCLED RUBBER SHEET  
8MM RECYCLED RUBBER GRANULES ENCAPSULATED IN A WEAR AND WATER RESISTANT ELASTOMERIC NETWORK. 2 PART
- 3. **BASE FINISH:** MILL
- 4. **POURED CONCRETE STAIRS:** NOSING SHALL TERMINATE NO MORE THEN 3" FROM END OF STEPS
- 5. **CONCRETE FILLED STEEL PAN STAIRS:** NOSING SHALL BE FULL LENGTH OF STEPS, LESS 1/8" CLEARANCE
- 6. **COLOR:** BLACK (STANDARD), SAFETY YELLOW, BLACK-BLUE, BLACK-GRAY
- 7. **LENGTH:** 12'0" MAXIMUM
- 8. **UL 1994 LISTED:** COMBINED WIDTH OF PHOTO-LUMINESCENT MATERIAL SHALL NOT BE LESS THAN 1"

LENGTH	QTY	COLOR

PROJECT:					
ARCHITECT:					
CONTRACTOR:					
QTY:					
PART#:		STSB-L1.875E-ECO			
 9300 73rd Avenue North Minneapolis, MN 55428		TITLE:			
		V431, Stair Tread, Recycled Rubber, Eco-Tread Long Nose, Alum Extruded Anchor			
	NAME	DATE	SIZE	DWG. NO.	REV
DRAWN	DKL	3/31/23	A	Nystrom STN STSB-L1.875E-ECO ShpDr	A
RELEASED	GLN	3/31/23	WEIGHT: .90 LB		SHEET 1 OF 1

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NYSTROM. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NYSTROM IS PROHIBITED.