


MODEL N3D

SPECIFICATIONS:

- ① **BASE:** EXTRUDED ALUMINUM ALLOY 6063 T-6
- ② **ABRASIVE:** ALUMINUM OXIDE SILICON CARBIDE GRANULES IN A UV PROTECTED, 2 PART EPOXY, LOCKED INTO EXTRUDED CHANNELS
- 3. **BASE FINISH:** MILL
- 4. **POURED CONCRETE STAIRS:** NOSING SHALL TERMINATE NO MORE THEN 3" FROM END OF STEPS
- 5. **CONCRETE FILLED STEEL PAN STAIRS:** NOSING SHALL BE FULL LENGTH OF STEPS, LESS 1/8" CLEARANCE
- 6. **COLOR:** BLACK (STANDARD), SAFETY YELLOW, GRAY, RED, BROWN, GREEN, BURGUNDY, BLUE, BUFF, LEADING EDGE ALWAYS LUMINESCENT
- 7. **LENGTH:** 12'0" MAXIMUM
- 8. **UL 1994 LISTED:** COMBINED WIDTH OF PHOTO-LUMINESCENT MATERIAL SHALL NOT BE LESS THAN 1"

LENGTH	QTY	COLOR

PROJECT:				
ARCHITECT:				
CONTRACTOR:				
QTY:				
PART#:		STSM-N3D		
 9300 73rd Avenue North Minneapolis, MN 55428		TITLE:		
		Stair Tread, Single Stage, 3 Abrasive Ribs, No Nose, Aluminum Extruded Anchor 1" Photoluminescent Strip		
NAME	DATE	SIZE	DWG. NO.	REV
DRAWN: DKL	10/24/23	A	Nystrom STSM-N3D ShpDr	A
RELEASED: GLN	10/24/23	WEIGHT: 1.27 LB		SHEET 1 OF 1