nystrom®

Top Security

ACCESS DOOR

Nystrom Top Security Access Door is manufactured with detention-grade materials and provides access through openings in walls. The pan style access door includes a heavy-duty butt hinge welded on the surface of the door to prevent unwanted access.

ORDER GUIDE

BASE	LATCH	WIDTH	X	LENGTH	OPTIONS
TS			**X**		
	D Detention Lock Prep **M** Mortise Lock (1 ⅛ inch) Prep	**Standard Sizes** (W x L) 12" x 12" 22" x 30" 24" x 40"* 16" x 16" 24" x 24" 24" x 48"* 18" x 18" 24" x 36"*			**G** Gasketing **M** Masonry Anchors **S** Stainless Steel, Type 304

Rough opening is door size + ½ inch minimum.
Additional sizes available, call for more information.
**Recommended for Wall surfaces only.*

DETAILS

DOOR 7 Gauge formed steel door

FRAME 3⁄16 inch Steel Angle - 2 inches by 3 inches

SIZE
- Min: 8 inches by 8 inches
- Max: 48 inches by 54 inches

INSTALLATION Ceiling or Wall

FLANGE 2" Exposed

HINGE Surface Mounted Heavy-Duty Butt

PAN DEPTH 1 ¼ inch

FINISH White Powder Primer Coat

Draft Stop

ACCESS DOOR

Nystrom Draft Stop Door is a non-rated access door designed to provide access through wall openings of draft stop spaces in the attic while preventing a back draft from one section of the attic to another. This self-closing and self-latching access door allows for access from both sides of the door.

ORDER GUIDE

BASE	FLANGE	LATCH	WIDTH	X	LENGTH	OPTIONS
D				**X**		
	T 1 inch Flange **W** Drywall Bead	**K** Knurled Knob/ Key Operated Latch Bolt **M** Mortise Lock (1 ⅛ inch) Prep	**Standard Sizes** (W x L) 12" x 12" 22" x 30" 24" x 40"* 16" x 16" 24" x 24" 24" x 48"* 18" x 18" 24" x 36"*			**B** Galvannealed **G** Gasketing **S** Stainless Steel, Type 304

Rough opening is door size +¼ inch. Additional sizes available, call for more information.
**Recommended for Wall surfaces only.*

DETAILS

DOOR 14 gauge Steel (self-closing)

FRAME 16 gauge Steel

SIZE
- Min: 6 inches by 6 inches
- DT Max: 24 inches by 72 inches, 36 inches by 60 inches or 48 inches by 48 inches
- DW Max: 36 inches by 48 inches

INSTALLATION Wall

FLANGE Exposed or Drywall Bead

HINGE
- DT: Flush Continuous Piano
- DW: Concealed Pin

FINISH White Powder Primer Coat